

MQ-19 High Contrast Film Developer

Material Safety Data Sheet

Date of issue: 05/30/2022

Revision date: N/A

Supersedes: N/A

Version: 1.0



SECTION 1: Identification

1.1. Identification

Product form : Solid powder
Substance name : MQ-19 High Contrast Film Developer
Chemical name : N/A - Mixture
CAS-No. : N/A - Mixture
Brand : Flic Film Inc.

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For photographic use only.
Recommended use : Photographic chemicals
Restrictions on use : Not for food, drug or household use

1.3. Supplier

Flic Film Inc.
10B Morrison Road, Longview, Alberta,
Canada T0L 1H0
T +1-403-982-4272

1.4. Emergency telephone number

Emergency number : +1-403-982-4272

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture GHS classification

Based on hydroquinone content

Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Germ cell mutagenicity Category 2	H341	Suspected of causing genetic defects
Carcinogenicity Category 2	H351	Suspected of causing cancer
Hazardous to the aquatic environment - Acute Hazard Category 1	H400	Very toxic to aquatic life

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

H302 - Harmful if swallowed
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H341 - Suspected of causing genetic defects
H351 - Suspected of causing cancer
H400 - Very toxic to aquatic life

Precautionary statements (GHS) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P261 - Avoid breathing dust
P264 - Wash exposed skin thoroughly after handling

MQ-19 High Contrast Film Developer

Material Safety Data Sheet

P270 - Do not eat, drink or smoke when using this product
P272 - Contaminated work clothing should not be allowed out of the workplace
P273 - Avoid release to the environment
P280 - Wear protective gloves, eye protection
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a poison center or doctor/physician
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P363 - Wash contaminated clothing before reuse
P391 - Collect spillage
P405 - Store locked up
P501 - Dispose of contents/container to comply with local, state and federal regulations

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Multi-constituent

Name	Product identifier	% w/w
Metol	(CAS-No.) 55-55-0	1-2
Hydroquinone	(CAS-No.) 123-21-9	5-10
Sodium sulfite	(CAS-No.) 7757-83-7	50-60
Sodium carbonate	(CAS-No.) 497-19-8	30-40
Potassium bromide	(CAS-No.) 7758-02-3	1-5

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Suspected of causing cancer.

First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : Suspected of causing genetic defects.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

Obtain medical assistance.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : N/A

5.2. Specific hazards arising from the chemical

No additional information available

MQ-19 High Contrast Film Developer

Material Safety Data Sheet

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Protective clothing. Gloves. Dust mask.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : On land, sweep or shovel into suitable containers. Minimize generation of dust. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid breathing dust. Obtain special instructions before use. Use personal protective equipment as required. Do not handle until all safety precautions have been read and understood.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container closed when not in use.
- Incompatible products : Acids and oxidizing agents.
- Incompatible materials : Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Component	Occupational Exposure Limits
Metol	No additional information identified.
Hydroquinone	ACGIH TWA 1mg/m ³ / OSHA PEL(TWA) 2mg/m ³ / US IDLH 50mg/m ³ / NIOSH REL (ceiling) 2mg/m ³
Sodium sulfite	No additional information identified.
Sodium carbonate	No additional information identified.
Potassium bromide	No additional information identified.

8.2. Appropriate engineering controls

- Appropriate engineering controls : Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation. Material should be handled using local exhaust ventilation (LEV) or laboratory hood whenever possible.

MQ-19 High Contrast Film Developer

Material Safety Data Sheet

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Chemical resistant apron. Gloves. Face shield. Protective clothing. Safety glasses.



Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or safety glasses

Respiratory protection:

Respiratory protection not required in normal conditions

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid.
Appearance	: Crystalline / powdery solid.
Colour	: Colourless to white. May discolour on exposure to light.
Odour	: None.
Odour threshold	: No data available.
pH	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: No data available.
Flash point	: No data available.
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: No data available.
Relative density	: No data available.
Specific gravity / density	: No data available.
Molecular mass	: N/A - Mixture.
Solubility	: Soluble in water.
Auto-ignition temperature	: No data available.
Decomposition temperature	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosion limits	: No data available.
Explosive properties	: No data available.
Oxidizing properties	: No data available.

9.2. Other information

No additional information available

MQ-19 High Contrast Film Developer

Material Safety Data Sheet

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

May discolour on exposure to air. May discolours on exposure to light.

10.3. Possibility of hazardous reactions

Do not add acids to MQ-19 Film Developer, since it may generate carbon dioxide and/or sulfur dioxide. Sulfur dioxide is an irritating and corrosive gas.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids or oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Nitrogen oxides. Sulfur dioxide.

11.1. Information on toxicological effects

Likely routes of exposure : Inhalation; Skin and eye contact

Acute toxicity : Oral: Harmful if swallowed.

MQ-19 High Contrast Film Developer mixture

LD50 oral rat	No data available.
---------------	--------------------

ATE US (oral)	No data available.
---------------	--------------------

Skin corrosion/irritation : Not classified.

Serious eye damage/irritation : Not classified.

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Hydroquinone is suspected of causing genetic defects.

Carcinogenicity : Hydroquinone is suspected of causing cancer.

MQ-19 High Contrast Film Developer mixture

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met. Harmful if swallowed.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Very toxic to aquatic life.

12.2. Persistence and degradability

MQ-19 High Contrast Film Developer mixture

Persistence and degradability	Not established.
-------------------------------	------------------

MQ-19 High Contrast Film Developer

Material Safety Data Sheet

12.3. Bioaccumulative potential

MQ-19 High Contrast Film Developer mixture

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to comply with local, state and federal regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

: No transport restrictions for small packages, i.e. these are small quantity kits and not regulated.

In accordance with DOT Transport document description

: UN3077 Environmentally hazardous substances, solid, n.o.s., 9, III

UN-No.(DOT)

: UN3077

Proper Shipping Name (DOT)

: Environmentally hazardous substances, solid, n.o.s.

Transport hazard class(es) (DOT)

: 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140

Packing group (DOT)

: III - Minor Danger

Hazard labels (DOT)

: 9 - Class 9 (Miscellaneous dangerous materials)



Dangerous for the environment

: Yes

Marine pollutant

: Yes



DOT Packaging Non Bulk (49 CFR 173.xxx)

: 213

DOT Packaging Bulk (49 CFR 173.xxx)

: 240

DOT Symbols

: G - Identifies PSN requiring a technical name

MQ-19 High Contrast Film Developer

Material Safety Data Sheet

DOT Special Provisions (49 CFR 172.102)	: 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies. 146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination. 335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s.," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging. A112 - Notwithstanding the quantity limits shown in Column (9A) and (9B) for this entry, the following IBCs are authorized for transportation aboard passenger and cargo-only aircraft. Each IBC may not exceed a maximum net quantity of 1,000 kg: a. Metal: 11A, 11B, 11N, 21A, 21B and 21N b. Rigid plastics: 11H1, 11H2, 21H1 and 21H2 c. Composite with plastic inner receptacle: 11HZ1, 11HZ2, 21HZ1 and 21HZ2 d. Fiberboard: 11G e. Wooden: 11C, 11D and 11F (with inner liners) f. Flexible: 13H2, 13H3, 13H4, 13H5, 13L2, 13L3, 13L4, 13M1 and 13M2 (flexible IBCs must be sift-proof and water resistant or must be fitted with a sift-proof and water resistant liner). B54 - Open-top, sift-proof rail cars are also authorized. IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2). IP3 - Flexible IBCs must be sift-proof and water-resistant or must be fitted with a sift-proof and water-resistant liner. N20 - A 5M1 multi-wall paper bag is authorized if transported in a closed transport vehicle. T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2) TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 155
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: No limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: No limit
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Other information	: No supplementary information available.

SECTION 15: Regulatory information

Canadian National Regulations

MQ-19 High Contrast Film Developer
Not listed on the Canadian DSL (Domestic Substances List)
Not listed on the Canadian IDL (Ingredient Disclosure List)

SECTION 16: Other information

Full text of H-phrases:	H302 Harmful if swallowed	H317 May cause an allergic skin reaction
	H318 Causes serious eye damage	H341 Suspected of causing genetic defects
	H351 Suspected of causing cancer	H400 Very toxic to aquatic life